LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 23 N. R. 12 W.	C-5, B-5, B-6, A-5
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on NOV. 3, 19 82, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C- CONTINUED.

~~A. Description of original monument and accessories and or subsequent restoration~~

B-6

FD 1/2" ROD W/RLS CAP #14102 &
SET CED POST W/LOC TAG.
*17" TW B CHERRY S50°W 84.22
*12" TW MAPLE S85°W 90.43
* 5" MAP CLUMP N10°E 67.93

CTR GRAVEL RD IN
CURVE EAST 48'±
*=SAME B.T.'S AS USED BY WILCOX

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-5 RECOVERED STD WEX CO MON PER WILCOX SURVEY OF SEC'S 7 & 18.
A-5 RECOVERED STD WEX CO MON PER WILCOX SURVEY OF SEC'S 7 & 18.
B-5 RE-ESTAB 1/4 COR COMM TO SEC'S 7 & 18 ON LINE & AT PRO-RATED DISTANCE TO U.S. (G.L.O.) SUR BETW FD NW & NE COR'S OF SEC. 18. FITS WILCOX SUB'N OF SEC. 18.
B-6 RECOVERED & ACCEPTED 1/2" ROD AS ESTAB BY WILCOX & ASSOC FOR CTR OF SEC. 18.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-5

FD WEX CO MON & SET
CED POST W/LOC TAG.
*4" BASSWD N50°W 15.91
*3" ELM S40°W 5.62
*4" MAPLE S45°E 17.08

*@ WILCOX B.T.'S FROM 1973

A-5

FD WEX CO MON & SET CED
POST W/LOC TAG.
*6" MAPLE N35°E 16.72
*6" " N66°W 17.51
*5" " S55°W 30.20
*11" CHERRY S60°E 13.45

WEST EDGE OF POWERLINE OPENING
IS EAST 50'±.
*=WILCOX 1973 B.T.'S.

B-5

SET DNR MON & CED POST.
8" MAPLE N66°W 3.3'
10" MAPLE N10°E 24.8
6" " N88°E 49.6
E-W TR RD NORTH 280'±

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

SIGNED BY Carl F. Roser 8-10-83 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

SPRINGVILLE TWP
WEXFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET