LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:		LOCATED IN—:		CORNER CODE NUMBER
1. PUBLIC LAND SURVEY		T. 23 N., R. 12 W.		B-3,A-3,
2. PROPERTY CONTROLLING IN SECTION	7	T. 23 N., R. 11 W.		1
3. MISCELLANEOUS PROPERTY IN SECTION	6	T. 23 N., R. 12 W.		632.2-W OF B-3
4. LOT NO.	, RECORDED PLAT			
5. PRIVATE CLAIMS				

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on AUGUST 3, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 12-27, 1982, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED

632.2-W

FD 1/2" RE-ROD (BY WILCOX & ASSOC.)

P. POLE	N30°W	26.03
5" ASH	S20°W	50.80
8" J PINE	S25°E	61.35

SET CED POST W/LOC TAG. NORTH 25'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-3 FD & ACCEPTED 1/2" ROD IN MON BOX FOR 1/4 COR COMM TO SEC'S 6 & 7. AN OLD N-S FENCE TO SOUTH IS 126'± WEST.

A-3 FD 1/2" RE-ROD THAT FITS TWO WILCOX B.T.'S. THE 6" MAP, N36°W, 55.50 HAD A PETE PERLA RLS TAG. THE CTR OF N-S POWER LINE IS 56' EAST.

1 ESTAB NW COR OF NE1/4 OF FRL NW1/4 OF SEC 7 AT PRORATED DISTANCE TO U.S.(G.L.O.) SURVEY & ON LINE BETW FD N1/4 COR & NW COR OF SEC. 7.

632.2 FD & ACCEPTED 1/2" RE-ROD FOR SE COR OF W1/2 - SE1/4 - SW1/4 OF SEC 6.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Fd. 1/2" rod B-3 in Mon. Box

*15" TW ASH	S45°E	92.30
*24" ELM STP	S70°W	127.11
P. POLE	N76°W	87.80

SET CED POST W/LOC TAG. SOUTH 33'

*=J. WILCOX B.T.'S

Fd. 1/2" re-rod. Replaced W/5/8"x36" A-3 rerod w/ACS Cap.

P.POLE	N50°E	78.38
*13" S PINE	S03°W	40.60
6" MAPLE	N36°W	55.50

SET CED POST W/LOC TAG. NORTH 33'

*12" MAPLE	N62°W	58.82

*=WILCOX B.T.'S.

1

DROVE 1" X 5" SOLID IR ROD		
26" CHERRY	N40°E	39.50
6" OAK	S16°E	44.93
P. POLE	S30°W	31.33

SET CED POST W/LOC TAG SOUTH 33'

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SIGNED BY Carl F. Roser 8-10-83 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SPRINGVILLE TWP.
Wexford County

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET