## LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 24 N. R. 9 W.	J-9; K-9; L-7; M-8	
2. PROPERTY CONTROLL- 24 ING IN SECTION	, <sub>T.</sub> 24 N. 8 9 W.	_16	
3. MISCELLANEOUS PROPERTY IN SECTION	,T N. E. W.		
4. LOT NO, RECO	ORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in li- re-established, monumented, re-n and rules therefore as required in Bureau of Land Management or l and 5 above were, in a field surve	nes 1 and 2 above were, in a monumented, recovered or re in the current manual of surve by a decree of a court of law, by on	field survey on	f P.A. 74, Michigan P.A. of 1970, 26 , 19 81, established, in conformance with regulations tates Department of the Interior, points mentioned in lines 3, 4 ored, established or re-established ation for Land Surveyors or, by a
— хххихжий ххий ххий ххий ххий хий хий хий хий х	ĸ <i>ĸ</i> ĸżąk kwekeka dak zaw	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	м о
C. Continued: L-7 Set DNR mon. & ced. po butter dish	st at fd. Fargo		M-8 non & added ced. post
14" Maple triple N5		w/loc tag. 9" Cedar	N75°W 23.9
	5°W 22.7	8" Cedar	N20°E 14.0
Fd 3/4" pipe (flush w/ E-W Rand line by other		10" Cedar S. edge of swp.	S60°E 18.0 South 90'±
W. edge Morrisy Ck. E	ast 216'	J. cage of smp.	30 <b>0</b> 011 30 1
	rth 28'		
BSwp. edge C-NW & SE Ea B Description of corner evidence J-9 Ed. Wexford Co. mon. a	e found and/or method appli	ied in restoring or re-establishing	g corner:
K-9 Fd. Wexford Co. mon. a	s set by J. Wilcox,	RLS, at position of re	ecovered 1" iron pipe re-
mains of cedar stake &	pieces of clay dish	<ul> <li>Irreg. rd. intersect</li> </ul>	tion N-S-E-W is 20'± North.
16 Fd. 1-2" rod, with RLS L-7 Restored 1/4 cor. at f	cap (J.L.W.), for N d Fargo (1913 for C	W cor. Of NEI/4-NeI/4 P C ) butter diches c	of Sec. 25.
which fits 1-Fargo Wit	, W.Pine stump 40"(r	emains) S39°E、66'. Cor	r. fits U.S. tie to swp.
edges E. & U.S. tie to	old Morrisy Creek st	ream bed 209'E. Fd. n	newer 3/4" pipe (in swp.)
30.0'N & 2.8"E which c they had both U.S. B.T M-8 Reestablished E1/4 cor C. Description of monument for	annot be proper Govt . remains & their co	. cor. as it falls in r. fits U.S. ties to s	swp. Fargo notes indicate
M-8 Reestablished E1/4 cor	. of Sec. 24 equidis	tant & on line bet. NE	a SE corners of S-24.
.]_9	K-	Q	16
Fd. Wexford Co. mon. & ad	ded Fd. Wexford Co	. mon. buried Fd 1/2	2" rod w/RLS cap #14102 &
ced. post w/loc tag	(U.5') 68   12" R Pine	adde N73°F 106 05 14" Ma	ed ced. post w/loc tag
* 9" R. Pine N62°E 98.	32 6" R. Pine	NO7°W 48.32 6" Ma	ple N15°W 24.00
ced. post w/loc tag  *36" Maple N17°W 25.  * 9" R. Pine N62°E 98.  * 9" R. Pine S36°E 88.  * = Old Wits	76 6" Cherry	\$23°W 64.28 * 9" W.	Birch \$30°W 15.58
* = UId WITS	Set ced. post	E. 50' * = 01d	Wits
	Ctr N-S dirt r	d. East 10'#	THE OF MICKE
$\wedge$ 17	$\bigcirc$		O.
SIGNED BY Carl 7.	Koses	DATE 5-11-8	F. ROSER
3.0.1.22			LAND
SURVEYOR'S MICHIGAN REC	ISTRATION NO. 120	28	SEAL NO. 12028
SIGNED BY 27.  SURVEYOR'S MICHIGAN REC  FOR STATE AND UNITED ST	ATES AGENCIES:		JAPPO LAND SHRINE
SIGNED BY	CHIEF OF BURNEY BANAN	DATE	
APPROVED AND SIGNED BY	Control PARIT	DATE	
	MICHIGAN REGISTERED LA	ND SURVEYOR	(SEAL)
		1 TD	ERTY TOWNSHIP
SURVEYOR'S MICHIGAN REC	ISTRATION NO		FORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975