

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

60

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. _____ E. _____ S., R. _____ W. _____	_____
2. PROPERTY CONTROLLING IN SECTION <u>27</u>	T. <u>1</u> N. _____ E. _____ S., R. <u>3</u> W. _____	H-10, H-9
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ E. _____ S., R. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Dwayne Scott, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on September, 1975, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- | | |
|---|--|
| <p><u>H-10</u> Recovered 1 1/2" Iron Pipe
Washtenaw Eng. Witnesses
Westerly 50', 12" Oak
Northerly 96', Twin 24" Oak
Easterly 68', 26" Cherry</p> | <p><u>H-9</u> Recovered 1 1/2" Iron Pipe
M.D.S.H. Witnesses
S58°W, 30.80', 7" Cherry
N40°W, 23.05', 8" Oak
N18°W, 20.75', 8" Oak
S45°E, 19.66', 13" Ash
S21°E, 26.77', 18" Hickory</p> |
|---|--|

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | |
|--|---|
| <p><u>H-10</u> Recovered 1 1/2" Iron Pipe
N80°W, 50.15', 10" Black Oak
N 75°E 21.92', 5" Black Oak
N05°W, 95.30', 24" Oak
S10°W, 17.40', 40" Oak
S45°E, 1.5' 6" x 6" Vertical
Steel Beam Fence Cor. Post</p> | <p><u>H-9</u> Recovered 1 1/2" Iron Pipe
N40°W, 23.05', 8" Oak
N18°W, 20.75', 8" Oak
S45°E, 19.66', 14" Cherry
S21°E, 26.77', 20" White Oak</p> |
|--|---|

SIGNED BY Dwayne Scott DATE November 6, 1975

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029