MAY - 1 1995

LAND CORNER RECORDATION CERTIFICATE			
COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970			
For corners in		•	l l Alan L L
Washtenaw	Located in:	Corner Code ##	mæ
(County)			- FO
	T 25 D 4E	M-10	ORCED W COUNTY, M H 17 MM '94
Public Land Survey	T <u>3S</u> R <u>4E</u> T R	W-10	POPUNT 17 AN ARRES
	T R		
	T R		10. 10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
2. Property Controlling			- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
in Section	S R		LIBER 1 PAGE JUKM
3. Miscellaneous	S T R		Register of Deeds States File Number
Property in Sec.	S T R		
•			
4. Lot No , F	Recorded Plat	<u></u>	ABCDEFGHIJKL
5. Private Claims			,
			2 5 5 4 3 2 7
			3
OL ALLO Wiles	March 2	0.4	4 - 7 - 8 - 9 - 10 - 11 - 12
Charles C. Wilson, in a field survey on March 3 19 94 5			
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned			
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land			
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 s 19 20 21 22 23 24			
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a			
Court of Law; established, i	re-established, monumented, re-r	monumented, recovered, found as	10 30 29 28 27 26 25
expressed below:			11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	orners, all in the same town ar	nd range, may be recorded	
on this certificate.			12 31 32 33 34 35 36
a positive de autobale.		d/or subsequent restoration:	13
A. Description of original monument and accessories and/or subsequent restoration:			
United States Government Survey,	1815 Instructions, Surveyed 1819, Bearing	ng Trees W.O. 12" S. 56 Links(36.96) W.O. 12" N22deg E 130 Links(85.8)	· 'n
		Meas. (N)(S) 40 Chains(2640)	<i>,</i>
11000. (11)(1) 10 010111(10 10)			
Washtenaw County Road Commission, William J. Armstrong, PS# 2444, September 11, 1935			
Found an Old Plow Point over a very Old Wood Stake. Reset with a Standard Concrete Monument.			
Continued on back:			
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:			
Found a 4* Concrete Monument in accordance with previously recorded accessories			
			<u>.</u>
•			*
•			•
C. Description of monume	ent for corner and accessories	established to perpetuate locatin	g the position of the corner:
O C A C C C C C C C C C C C C C C C C C			
Collect (197-10) Collected Principality White Collected			
Comer (M-10) Concrete Montinent with R1 and Continued on back:			
Continued on cases:			
CHARLES C.			
WILSON NO 13604			
CHARLES C. WILSON NO 13604			
	ROLLISTONAL SURVEYOR		
	LOS CORVE		
	PAGE STONAL SURVEYOR		
/			1 1004
Signed by	al C. We	DateMay	1, 1994
Surveyor's Michigan Licens	se No. 13604		APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
Surveyors Michigan Licens	po 140.	FOHN	REVISED MAY 14, 1975 REVISED JAN., 1983

A. Paragraph A. Continued:

William J. Armstrong PS# 2444 September 11, 1935 12" W. Oak S70deg E 130.0 12" W. Oak S36deg E 57.4 2" Elm S10deg E 115.3 10" B. Cherry S75deg W 39.2 10" B. Cherry S87deg W 59.5

Washtenaw Engineering Co., Inc. Norman N. Fahrner PS# 17620 Act 74 Recordation, Liber 1, Page 25 Found Concrete Monument 24" Oak \$70deg.E 129.7 § 24" Oak \$36deg.E 55.8 Power Pole N60deg.W 122.4

Survey September 10, 1985
Found Concrete Monument
28" W. Oak S70deg.E 130.0
32" W. Oak S36deg.E 57.4
Power Pole N60deg.W 123.0
On Fence W'ly, 1.2 E of Fence N-S
60' N. of center of traveled Weber Road, Gravel

C. Wilson & Associates, Inc. Charles C. Wilson PS# 13604 Survey 1987 16" W. Oak S70deg.E 130.0 16" W. Oak S36deg.E 57.4 16" B. Cherry S75deg.W 39.2 16" B. Cherry S87deg.W 59.5

C. Paragraph C. Continued:

Stump S75deg.W 39.2
On Fence W'ly, 1.2 E. of Fence N-S
60' N. of center of traveled Weber Road, Gravel
Chisel Hole in Large Flat Stone S40deg.W 23.80
Twin 18" Elm S15deg.E 235.64(Nail & RT W/S)
Top of RR Tie Fence Post S20deg.E 99.48(Nail & RT)
8" Elm N'ly 31.16(Nail & RT E/S)
Power Pole N'ly 52.96(Nail & RT E/S)
38" Forked Maple S85deg.E 473.25(Nail & RT /S)
SE Cor. of Chimney at ground(House #8422)N40deg.W 169.49

I find no evidence to conflict with the acceptance of this found corner as being a careful and faithful perpetuation of the position of the origanal corner.

This corner was ratified by the Washtenaw County Peer Committee on March 8, 1994

0.3