Signed by _

Surveyor's Michigan License No. 13604

MAY - 1 1995		•		
COMMISSION		ER RECORDATION CERTI	6 .	WASH WASH
For corners in	Filing-Requir	rement of Act 74, Mich. P.	A. 1970	
Washtenaw	Located In:	Corner Code ##		EX NE NE
(County)				
Public Land Survey	T 3S R 4E	M-12	A AAN	GOUNTY. H
	T R T R		Signal Si	
	T R		g	£ =
· · ·	T R T R		LIBER 1 PAGE 3	7RM
	T R		Register of Deeds Star	ok File Number
Property in Sec. S _	T R		riogister of secus often	ippa i ne italizer
4. Lot No, Recorde	ed Plat		A B C D F	
5. Private Claims			A B C D E	FGHIJKL
	•		3 5 5 7 3	3 - 2 - 1 -
			4 7 8 9)101112-
	ield survey on Septemb		5	- - - - - - - - - -
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the				
current manual of survey instructions Management or by a decree of a Court of	•	· · · · · · · · · · · · · · · · · · ·	1 1 1 1	
above were in conformance with the ru	les of the Michigan Board o	of Land Surveyors or by a Decree	e of a	1222324
Court of Law; established, re-estable expressed below:	ushed, monumented, re-i	monomented, recovered, round	10 30 29 2	8-27-26-25-
NOTE: Not more than 4 corners,	all in the same town as	nd range, may be recorded	11	
on this certificate.			12 31 32 3	3 34 35 36
A. Description of original monum	ent and accessories and	d/or subsequent restoration:		
United States Government Survey, 1815 Inst	ructions, Surveyed 1819, Bearing	B.O. 6" N25deg.W 37 Links(2: Meas. (N) 40 Chains(2640)		•
		40 Chains(2640)		
Washtenaw County Road Crimission, Willia Found a Flat Sharp Stone over an Old Wood Reset with a standard 4"x48" Concrete Monu	Stake, surrounded by a Group of			
		Continued on back:		
B. Description of corner evidence	found and/or mothed :	annlied in restoring or reesta	ablishing corper	
·		-		
Found a 4" Concrete Monument with a 1/4". Saline-Waterworks Road (E-W) Gravel, 8" b William J. Armstrong in 1935. This point co	elow road surface. I believe this	s to be the Concrete Monument set by		•
		•		,
				•
C. Description of monument for c	orner and accessories e	established to perpetuate loc	cating the position of the con	ner:
Corner (M-12) 4" Concrete Monument with I feel that this corner, as found, is a careful This corner was ratified by the Washtenaw	and faithful perpetuation of the	position of the original corner.	ed #13604	CN/C
		Continued on back:	CHARLE	s C

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

POTES, ONAL

Date _

May 1, 1994

WILSON NO 13604

SURVE

A. Paragraph A. Continued:

William J. Armstrong PS# 2444 October 11, 1935 5" B. Ash N18deg.E 70.3 2" Apple N87deg.E 100.8 16" Hickory S4deg.E 251.1 Clump of Ash N16-1/2deg.E 64.5 Twm 2" Elm S61deg.W 50.0 2" Hickory N74-1/2deg.W 69.7 Comer (A-12) T4S, R5E, S'ly 12.3

Atwell-Hicks, Inc., Book 548, Page 47
September 12, 1992.
Found Concrete Monument
Power Pole S60deg.E 54.72(nail NE/S)
15" Oak S30deg.E 73.42(nail W/S)
15" Hickory N50deg.W 69.67(nail S/S)
1-1/2" Iron Pipe corner (A-12) T4S, R5E, S'ly 11.91

C." Paragraph C. Continued:
22" Ash N18deg.W 70.30 (Nail & RT W/S)*
Power Pole S45deg.E 54.87(Nail & RT NE/S)*
18" Oak S15deg.E 743.40(Nail & RT W/S)*
14" Hickory N70deg.W 69.67(Nail & RT S/S)*
60" Oak N80deg.W 226.64(Nail & RT S/S)
Twin 16* Oak S10deg.W 299.21(Nail & RT E/S)
1-1/2" Iron Pipe, corner (A-12) T3S, R5E, S1y 11/91*
1-1/4" Iron Pipe, corner (M-13), T3S, R4E, S1y 2689.18

* indicates accessory previously mentioned in Paragraph A.

LIBER 1 PAGE 38RM - CUPY -