

-copy-

MAY 09 1996 COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

M-13 Page 1

For corners in Wayne Wash Haven County

Located in: YPSILANTI Corner Code

1. Public Land Survey

T 3 S R 7 E T 4 S R 7 E

M-13 M-1

2. Property Controlling In Section

S T S T S T S T

3. Miscellaneous Property in Sec.

S T S T S T S T

Register of Deeds Stamp and File Number

4. Lot No. Recorded Plat 5. Private Claims

Grid table with columns A-M and rows 2-13 containing numbers 1-36.

I, Michael S. Hoben in a field survey on 03/01/1995 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management, or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restorations:

11/24/1816 NO RECORD FOUND G.L.O. POST

01/01/1930 1 ED. GUY POLE NW, 27.80' (A-13 VANBUREN) W.C.R.C. MON. (A-13 VANBUREN TWP.)

( Witnesses Continued on Back ... )

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MON IN MON BOX IN ASPH. RD.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

03/01/1995 Hoben 35994 OHM REMON

- 7 C.L. CATCH BASIN S 51 E 33.23'
8 C.L. CATCH BASIN S 51 W 34.70'
10 TAG IN DE POLE N 40 E 73.21'
11 TAG IN DE POLE N 45 E 82.65'
12 SET TAG IN DE POLE S 30 E 158.02'



RECORDED WASHTEWAY COUNTY, MI MAR 29 1 50 PM '96

We conclude that after careful study of the record documentation and field observations, that this corner is accepted as the best available evidence of the position of the original corner.

Signed by Michael S. Hoben

Date 12-18-95

Drafted by Michael S. Hoben Surveyor's Michigan License No. 35994

Orchard, Hiltz and McCliment, Inc. 34935 Schoolcraft Road Livonia, MI 48150

A. (Continued) Description of original monument and accessories and/or subsequent restorations:

01/01/1930 W.C.R.C. 11 2... MON. (A-13 VANBUREN TWP.)

- 2688.74' S. OF W. 1/4 COR. SEC. 31 VANBUREN TWP. (A-12)
- 2 ED. POLE NE. 38.17' (A-13 VANBUREN)
- 3 NAIL NE. SIDE FENCE POST SE. 35.68' (A-13 VANBUREN)
- 4 NAIL NW. SIDE 12" BOX ELDER SW. 61.32' (A-13 VANBUREN)
- 5 U.S.G.S. MON. SW. 41.80' (A-13 VANBUREN)

11/20/1972 J. SNYDER 13352 ATWELL-HICKS L.2 P

FOUND 1/4" RE ROD IN MON. BOX AT C. LINE RD. INT.

- 6 12" APPLE N.56 W. 61.5'
- 7 CATCH BASIN S 51 E. 33.2'
- 8 CATCH BASIN S. 51 W. 34.7'

03/20/1978 R. JAGOW 6998 ATWELL-HICKS

1/4" REROD IN MON. BOX @ CL. INT. RAWSONVILLE & BEMIS

SAME AS ABOVE

APPROVED  
 DATE 10/16/95  
 CO. REP. KA